



The dispense tip helps define the deposit shape and the performance of your dispenser. Whether using an AirFree® or AirPulse™ dispenser any dispense tip will attach to your dispense component.


TAPERED FREEFLOW™



Precision taper allows fluid to flow without restriction, reducing stringing and ooze. Polyethylene molded with UV light block. These tips feature the PosiLok™ hub.

1,000 per pack

GAUGE	FLEXIBLE	RIGID
14G	E415151	E405151
16G	E415131	E405131
18G	E415111	E405111
20G	E415091	E405091
22G	E415071	E405071
25G	E415041	E405041




PRECISELY BENT STAINLESS STEEL

PosiLok™ polypropylene hub with polished 304 stainless steel tubing is cut burr free. Bent at 45 and 90 degree angles.

1,000 per pack

GAUGE	.5" LONG	.5" LONG	1.5" LONG
	45° ANGLE	90° ANGLE	45° ANGLE
14G	E501151	E601151	E503151
15G	E501141	E601141	–
16G	E501131	E601131	–
18G	E501111	E601111	E503111
19G	E501101	E601101	–
20G	E501091	E601091	–
21G	E501081	E601081	E503081
22G	E501071	E601071	–
23G	E501061	E601061	–
25G	E501041	E601041	–
27G	E501021	E601021	–
30G	E501010	E60101	

PERFECTLY STRAIGHT




Stainless Steel

PosiLok™ polypropylene hub with polished 304 stainless steel tubing is cut burr free.

1,000 per pack

GAUGE	.25" LONG	.5" LONG	1" LONG	1.5" LONG
14G	E019151	E011611	E012611	E013611
15G	E019141	E011141	E012141	E013141
16G	–	E011131	E012131	E013131
18G	E019111	E011111	E012111	E013111
19G	–	E011101	E012101	E013101
20G	E019091	E011091	E012091	E013091
21G	E019081	E011081	E012081	E013081
22G	E019071	E011071	E012071	E013071
23G	E019061	E011061	E012061	E013061
25G	E019041	E011041	E012041	E013041
27G	E019021	E011021	E012021	E013021
30G	E019011	E011010	–	–



STRAIGHT BUT FLEXIBLE

Soft polypropylene burr and flash free tips assure accurate deposit control. Recommended for use with fluids that react with metals or to prevent scratching.

1,000 per pack

GAUGE	.5" LONG	1.5" LONG
15G	E281141	E283141
18G	E281111	E283111
20G	E281091	E283091
25G	E281041	E283041

PosiLok™ Tip Bulk Disposable Dispense Tips



THICK PASTE

PosiLok™ polypropylene hub with polished 304 stainless steel tubing is cut burr free. .25" length designed for filled or thick pastes.

1,000 per pack

GAUGE	.25" LONG
14G	E889151
15G	E889141
16G	E889131



FINE SURFACE

PosiLok™ polypropylene hub with polished 304 stainless steel tubing is cut burr free. Chamfered tip reduces surface tension allowing easy deposit of fluid on fine surfaces.

1,000 per pack

GAUGE	.5" LONG
18G	E341111
23G	E341061
25G	E341041



MICRODOT

PosiLok™ polypropylene hub with polished 304 stainless steel tubing is cut burr free. Small gauge designed for microdot dispensing.

1,000 per pack

GAUGE	.25" LONG	.312" LONG	Hub Color
27G	E019021	E01Y021	Clear
30G	E019011	E01Y011	Lavender
32G	E019411	—	Yellow



UV LIGHT SHIELD

One piece shield slides over the tip blocking light from penetrating the PosiLok™ polypropylene hub. Fits on the end of the syringe ideal for UV and light sensitive adhesives.

1,000 per pack

BARREL SIZE	PART #	COLOR
5CC	A560C21	Black
3,10-55CC	A550C21	Black



TEFLON® LINED

Teflon® burr and flash free tips assure accurate deposit control. Recommended for use with fluids that react or bond with metals such as cyanoacrylates. Teflon Lined Tips prevent scratching.

1,000 per pack

ID	.5" LONG	COLOR
0.020"	E031081	Grey
0.006"	E031041	Pink

Refer to the various selection guides or for more information on Fishman's® dispensing capabilities, contact one of our Customer Service Representatives for assistance at (800) 433-2115.